



BLUE STAR



CXYF Series
Split AC

فئة CXYF
مكيف سبليت


CXYF Series Split AC

R410A

Rotary



1.5TR / 2.0TR / 2.5TR CXYFA / CXYFB



3.0TR CXYFA

Key Features:



تبريد صديق للبيئة
R410A
Eco Friendly
Refrigerant - R410A



تأرجح رباعي الابعاد
أوتوماتيكي
Automatic 4D
Swing



تبريد حتى في درجة حرارة
00 درجة مئوية
Cools even
at 55°C



مكثف مضادة للتآكل
الزعانف النحاس الذهبية
Anti-corrosive
Gold Fin Copper
Condenser



تبريد التوربو
Turbo Cooling



وضع النوم
Sleep Mode



عرض مخفي
Hidden Display



٢ مخرج مرن للإخراج
2 Way Flexi Drain
Connection



مبخر ماء الزعنفة الذهبية
Hydrophilic Gold
Fin Evaporator



نظام توفير الطاقة
Energy Saving
Mode

Certifications:



ESMA
Certified



EWA
Certified



GSO
Certified



PAI
Certified



G MARK
Certified



CB
Certified



ECAS
Compliant



RoHS
Compliant



Eco-friendly Refrigerant



Blue Star's split air conditioners use environment friendly refrigerant like R410A which exhibits zero ozone depleting properties along with Polyolester (POE) which provides superior heat transfer capabilities, better lubrication and better oil return properties. The R410A refrigerant, which is wax-free is also safe for use in the environment.



Gold Fin Evaporator

Hydrophilic evaporator fins prevent accumulation of water and dust particles on the coil thus prevnts growth of bacteria and fungi and maintaining the healthy air quality in the air conditioned space.



Gold Fin Condenser

Special anti-corrosive gold fins in the copper condenser ensure better resistance to corrosion and to increase the life of air conditioners making it heavy-duty.



Automatic 4D Swing for Uniform Cooling across the Room



Automatic 4D Swing with airflow directional control helps the user adjust the horizontal as well as the Vertical swing or even stop at a particular angle. This adds to the users' comfort by letting them manage the airflow direction to suit their needs and avoid a direct draught of cold air.



Cools even at 55°C



Unlike normal air conditioners that operate till 46°C, Blue Star's T3 air conditioners are robust enough to work even at a peak temperature of 55°C.

CXYF Series Split AC

R410A

Rotary

UAE	Nominal Capacity	1.5 TR	2 TR	2.5 TR	3 TR
	Model	HW18CXYFB3-01	HW24CXYFB3-01	HW30CXYFA3-01	HW36CXYFA3-01
	Energy Efficiency Class	3 Star	3 Star	2 Star	2 Star
Performance Parameters	Voltage / Frequency / Phase	220-240 V / 50Hz / Single			
	Rated Cooling Capacity (BTU/h) @ T3	16000	19000	21750	26200
	Rated Power Input (W) @ T3	1776	2109	2503	3014
	Rated EER - (BTU/hW) @ T3	9.01	9.01	8.69	8.69
Performance Parameters	Rated Cooling Capacity (BTU/h) @ T1	18000	22000	25000	30800
	Rated Power Input (Watt) @ T1	1512	1818	2070	2550
	Rated EER - (BTU/h/Watt) @ T1	11.90	12.10	12.08	12.08
Indoor	Filter Configuration	Dust Filter			
	Evaporator	Hydrophilic Gold Fin			
	Air Flow (Wet CFM) (Turbo/High/Medium/Low)	649/581/510/466	649/581/510/466	760/760/660/540	1000/980/870/790
	Noise Level (Turbo/High/Medium/Low) in dB(A)	49/46/43/38	51/48/44/40	49/49/47/45	53/51/49/43
	Dimension (W x H x D) mm	1010×315×220	1010×315×220	1186×340×258	1460×349×285
	Net Weight (kg)	13	14	18	22
Outdoor	Condenser	Anti Corrosive Gold Fin Copper Condenser			
	Noise Level in dB(A)	53	55	58	58
	Dimensions (W x H x D) mm	920 × 699 x 380	920 × 699 x 380	953 x 808 x 433	953 x 808 x 433
	Net Weight (kg)	43	45	58	58
Tube Size	Suction Tube Size Outer Diameter (mm / inch)	Φ 12.7 (1/2")	Φ 15.88 (5/8")	Φ 15.88 (5/8")	Φ 15.88 (5/8")
	Liquid Tube Size Outer Diameter (mm / inch)	Φ 6.35 (1/4")	Φ 6.35 (1/4")	Φ 9.52 (3/8")	Φ 9.52 (3/8")
Max Ambient Operating Temperature (°C)		55	55	55	55
Input Power Supply		Indoor	Indoor	Indoor	Outdoor

*Blue Star has a policy of continuous product and product data improvement and reserves the right to change design and specifications without notice.

* Piping Height after 5m need professional installation to keep check on oil return to compressor and additional gas charge as specified in manual.

Rotary

R410A

مكيف سبليت فئة CXYF

3 TR	2.5 TR	2 TR	1.5 TR	قدرة المكيف	الإمارات
HW36CXYFA3-01	HW30CXYFA3-01	HW24CXYFB3-01	HW18CXYFB3-01	نموذج	
2 نجوم	2 نجوم	3 نجوم	3 نجوم	فئة كفاءة الطاقة	
220-240 V / 50Hz / فردي				الجهد / التردد / المرحلة	قياسات الآداء
26200	21750	19000	16000	سعة التبريد المقدرة (وحدة حرارية بريطانية/ ساعة) على 3 طن	
3014	2503	2109	1776	مدخلات الطاقة المقدرة (واط) على 3 طن	
8.69	8.69	9.01	9.01	تصنيف إي إي آر (وحدة حرارية بريطانية/ ساعة) على 3 طن	
30800	25000	22000	18000	سعة التبريد المقدرة (وحدة حرارية بريطانية/ ساعة) على 1 طن	قياسات الآداء
2550	2070	1818	1512	مدخلات الطاقة المقدرة (واط) على 1 طن	
12.08	12.08	12.10	11.90	معدل إي إي آر - (وحدة حرارية بريطانية/ ساعة) على 1 طن	
مرشح غبار				مواصفات تنقية الهواء	داخلي
الزعنفة الذهبية القابلة للماء				المبخر	
1000/980/870/790	760/760/660/540	649/581/510/466	649/581/510/466	تدفق الهواء (عالي/ متوسط / منخفض/توربو) (Wet CMH)	
53/51/49/43	49/49/47/45	51/48/44/40	49/46/43/38	مستوى الصوت (عالي/ متوسط / منخفض/توربو) في dB (A)	
1460x349x285	1186x340x258	1010x315x220	1010x315x220	أبعاد الوحدة (عرض / ارتفاع / عمق) مم	
22	18	14	13	الوزن الصافي (ك ج)	
الزعنفة الذهبية المضادة للتآكل				المكثف	خارجي
58	58	55	53	مستوى الصوت في dB (A)	
953 x 808 x 433	953 x 808 x 433	920 x 699 x 380	920 x 699 x 380	أبعاد الوحدة (عرض / ارتفاع / عمق) مم	
58	58	45	43	الوزن الصافي (ك ج)	
Φ 15.88 (5/8")	Φ 15.88 (5/8")	Φ 15.88 (5/8")	Φ 12.7 (1/2")	مقاسات الخارجية للأنبوب الشفط (انش/مم)	مقاس الأنبوب
Φ 9.52 (3/8")	Φ 9.52 (3/8")	Φ 6.35 (1/4")	Φ 6.35 (1/4")	مقاسات الخارجية للأنبوب السائل (انش/مم)	
55	55	55	55	أقصى درجة حرارة التشغيل المحيطة (درجة مئوية)	مدخلات امداد الطاقة
خارجي	داخلي	داخلي	داخلي		

* تتبع بلو ستار سياسة التحسين المستمر للمنتجات و بيانات المنتج وتحقق بحققها في تغيير التصميم والمواصفات دون سابق إنذار
* ارتفاع الأنابيب بعد 5 أمتار يحتاج إلى تثبيت احترافي للحفاظ على فحص الزيت عند العودة إلى الضاغط وشحنة غاز إضافية كما هو محدد في الدليل.



Authorised Distributor

For more information, please contact:

Dubai : Tel. 04 203 6888
Sharjah : Tel. 06 533 1513
Fujairah : Tel. 09 222 3187
RAK : Tel. 07 222 3622
Mussafah : Tel. 02 555 4401

الشركة التجارية المركزية ذ.م.م.
CENTRAL TRADING COMPANY L.L.C.
Established 1957



A Member of Al Rostamani Group

E-mail: sales@ctc-uae.com Web: www.ctc.ae