



FEATURES

















Faster cooling

Tropicalised for 50°C ambient

Silent operation

Food grade body

Tropicalised SS tank and reciprocating compressor

Elegant chrome Eco-friendly plated taps

refrigerant

resistant outer body

Technical Specifications

Model		PN096GSSBP4TR01	PN165GSSBP4TR01
Performance Parameter	Peak Cooling Capacity (USG)	96	165
	Storage Tank Capacity (USG)	60	125
	Storage Tank Capacity (Litres)	227	473
	Cooling Capacity (USG) At 35°C / 30°C Water Inlet / 15°C Water Outlet	39	40
	Cooling Capacity (Litres) At 35°C / 30°C Water Inlet / 15°C Water Outlet	148	151
	Power Supply		
	Input Power (Watts)	1550	1550
	Current (Amps)	7.3	7.3
	Max Ambient Temperature	50°C	50°C
	Puff Thickness	PUF (CFC Free) - 40mm (Approx.)	PUF (CFC Free) - 40mm (Approx.)
	No. of Taps	4	4
Tank	Tank Material	SS-304	SS-304
Constrution Material	Front Panels	SS-304	SS-304
	Side Panel	SS-304	SS-304
	Back Panel	Pre-coated Sheet	Pre-coated Sheet
	Top Panel (Close Type Lid)	SS-304	SS-304
	Drip Tray	SS-304	SS-304
	Anti-splash Tray	SS-304	SS-304
Drainage	Drainage Location	Bottom	Bottom
Compressor and Refrigerant	Compressor Type	Reciprocating	Reciprocating
	Blowing Agent	R141-B	R141-B
	Refrigerant Type	R 134A	R 134A
Dimensions and Net Weight	Dimensions (W x D x H) mm	820 x 1235 x 710	1120 x 1500 x 745
	Net Weight (Kg)	110	130

^{*}Blue Star has a policy of continuous product and product data improvement and reserves the right to change design and specifications without notice.



For more information, please contact:

Dubai : Tel. 04 203 6888 Sharjah : Tel. 06 533 1513 **Fujairah** : Tel. 09 222 3187 RAK : Tel. 07 222 3622 Mussafah: Tel. 02 555 4401

Authorised Distributor



E-mail: sales@ctc-uae.com Web: www.ctc-uae.com