

# MICHELIN LT AGILIS

7.00R16 LT 117/116L - 7.50R16 LT 122/121L - 8.25R16 LT 128/126K

**The leader of all position  
light truck tyre for on-road operations**

- ▶ Long Life
- ▶ Excellent Grip
- ▶ Reliability

HIGHWAYS - ROADS - URBAN



**MICHELIN LT AGILIS**  
*All Position*





# The leader of all position light truck tyre for on-road operations


## MICHELIN LT AGILIS

7.00 / 7.50 / 8.25 R16 LT




### Long Life

- 5% wider tread compared to MICHELIN XZA range.



### Excellent Grip

- 3D sipes interlock in the tread blocks for **excellent rigidity and grip on all road surfaces** to the last millimeter.
- 3D self-blocking sipes to reduce uneven wear



### Reliability

- Michelin Truck casing with **crown and sidewall protections**
- Cool running tread compound to **minimize over heating**
- New sidewall** design to have better aggression resistance
- Regroovable** tread band

MICHELIN Durable Technologies

## MICHELIN technical truck tyre data :

Load per axle kg		Inflation		Load index Speed symbol	Unique point	Dimensional characteristics					New tyre tread depth	Advised rims	Flaps (New flaps 2000)	Tubes
Simple	Twinned	Bar	PSI			Dimensions E.T.R.T.O			MICHELIN dimensions					
Kg	Kg					S	D	CdR/RC	R'	E				
						mm	mm	mm	mm	mm				
<b>7.00 R 16 LT AGILIS TL</b>														
2 000	3 890	4.5	65	117/116L (PR12)		204	795	2391	366	220	9.2 mm	4.50E SDC	16X6.00	16J
2 190	4 260	5.0	75									5.00F SDC		
2 380	4 630	5.5	80									6.00G SDC		
2 570	5 000	6.0	85									5.50F - 6L		
<b>7.50 R 16 LT AGILIS TL</b>														
2 030	3 930	4.5	65	122/121L (PR14)		216	814	2460	377	238	9.2 mm	6.0	16X6.00	16J
2 230	4 300	5.0	75									5.50F SDC		
2 420	4 680	5.5	80									6.00G SDC		
2 610	5 050	6.0	85									6.50H SDC		
2 810	5 430	6.5	95									5.50F 6L		
3 000	5 800	7.0	100									6 ½L		
<b>8.25 R 16 LT AGILIS TT</b>														
2 760	5 210	5.0	75	128/126K		237	874	2623	399	262	10.5 mm	6.00G SDC	16X6.00	16J
3 000	5 670	5.5	80									6.50H SDC		
3 240	6 120	6.0	85									6.00		
3 480	6 570	6.5	95									6.50		
3 600	6 800	6.75	100											

**Warning :** Serious or fatal injury may result from tyre failure due to incorrect selection, fitting, usage or maintenance of tyres. To ensure correct selection, fitment, usage and maintenance, refer to your Michelin local contact. Please consult tyre professionals for all tyre related issues.

**Notice :** Availability of products shown in this document may vary from country to country. Please consult your local MICHELIN contact before proceeding.

