

X[®] MULTI[™] TROPIC Z

325/95 R 24 (=12.00 R 24) Tubeless 162/160K*

BUILT TO LAST

- 25%* Stronger Tyre Summit
- 10%* more Mileage performance



 **X[®] MULTI[™] TROPIC Z**

325/95 R 24 (=12.00 R 24)
Tubeless 162/160K*



BUILT TO LAST



X MULTI™ TROPIC Z



+25% SUMMIT ENDURANCE



Advantages

New summit architecture for cooler running


Super High Tensile cables used in tread

Benefits

Increased strength
Less break down
Timely deliveries



+10% MILEAGE PERFORMANCE & EVEN WEAR



Advantages

Increased tread width

New rib pattern design and robust sipes

Benefits

Better even wear
Increased resistance to aggressive trailer application

MICHELIN technical truck tyre data:

Tread Pattern	Load index/ Speed symbol	Section Width	Free diameter	Laden radius	Minimum dual spacing	Advised Rims	S=Single T=Twinn	Pressure (Bars) Load per axle (kg)										
								6,00	6,25	6,50	6,75	7,00	7,25	7,50	7,75	8,00	8,25	8,50
X Multi Tropic Z	162/160K	312	1214	560	355	8.5	S	7090	7350	7610	7870	8140	8400	8660	8920	9190	9450	9500
							T	13430	13920	14420	14920	15410	15910	16410	16910	17400	17900	18000

*Please consult your local MICHELIN contact for more details.

